



MATERIAL SAFETY DATA SHEET

PRODUCT : RUXX OIL PREMIUM SYNTHETIC
(S.A.E 10W/40 API SM/CF)
CODE : UGL17ABXXYY
COMPANY IDENTIFICATION : M/s UNITED GREASE AND LUBRICANTS
P.O. BOX 2685
AJMAN
U.A.E.
EMERGENCY PHONE NUMBER: 00971-6-7436521
PRODUCT USE : PREMIUM SYNTHETIC GASOLINE ENGINE OIL

COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	WT %
Calcium branched alkylphenol and overbase sulfonates	2-6%
Zinc Alkyl dithiophosphates	0-1.5%
Organo molybdenum amide	0.5
Distillates (petroleum), hydro treated light paraffinic	50-60%

HAZARDS IDENTIFICATION

HAZARDS : UNDER NORMAL CONDITIONS OF USE, THIS PRODUCT SHOULD NOT CAUSE ANY SIGNIFICANT HEALTH HAZARDS. HOW EVER A PROLONGED USE MAY CAUSE DERMATITIS.

FIRST AID MEASURES :

SKIN CONTACT : REMOVE CONTAMINATED CLOTHING, WASH SKIN IMMEDIATELY WITH WATER AND SOAP

EYE CONTACT : FLUSH WITH LARGE AMOUNT OF WATER, GET MEDICAL ATTENTION IF IRRITATION PERSISTS

INGESTION : DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION

INHALATION : IN CASE OF EXPOSURE TO HIGH CONCENTRATION REMOVE PERSON TO FRESH AIR

FIRE FIGHTING MEASURES





الشركة المتحدة للشحوم و الزيوت ذ.م.م. UNITED GREASE & LUBRICANTS Co. L.L.C.

FLASH POINT : 224 Deg C
EXTINGUISHING MEDIA : CO₂, DRY CHEMICAL, OR FOAM. WATER SPRAY, DO NOT USE WATER JETS. THEY COULD CAUSE SPLATTERING.

ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PROTECTION : SHUT OFF SOURCE OF SPILL. RECOVER FREE LIQUIDS BY USING APPROPRIATE TECHNIQUES. NOTIFY LOCAL AUTHORITIES
HANDLING AND STORAGE : HANDLING AND STORAGE TEMP. AMBIENT TO 85 Deg C

EXPOSURE CONTROLS/PERSONAL PROTECTION.

HAND/EYES/SKIN PROTECTION : WEAR GOGGLES, PROTECTIVE CLOTHING, GLOVES.
VENTILATION : NO SPECIAL VENTILATION REQUIRED

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE : C&B
ODOUR : CHARACTERISTIC
COLOR : GOLDEN
DENSITY @ 15 Deg : 0,885 g/ml
FLASH POINT : 224 Deg C
SOLUBILITY : SOLUBLE IN HYDROCARBON SOLVENTS, INSOLUBLE IN WATER

STABILITY AND REACTIVITY

STABILITY : STABLE PRODUCT
HAZARDOUS REACTION : NONE
ECOLOGICAL INFORMATION
GENERAL : NO SPECIFIC ENVIRONMENTAL DATA AVAILABLE

DISPOSAL CONSIDERATION

DISPOSAL OF PRODUCT : DO NOT DISPOSE OF THE PRODUCT EITHER NEW OR USED, BY DISCHARGING IN TO SEWERS, TUNNELS, LAKES OR WATER COURSES.

TRANSPORT INFORMATION

NOT DANGEROUS FOR CONVEYANCE
UNDER UN, IMO, ADR/RID AND : NOT REGULATED
IATA/CAO CODES

REGULATORY INFORMATION:



ISO 9001: 2008
Reg No : RI91/6709

ص.ب: ٢٦٨٥، عجمان - ا.ع.م.، تليفون: ٠٠٩٧١-٦-٧٤٣٦٥٢١، فاكس: ٠٠٩٧١-٦-٧٤٣٩٧٠٩
P.O. Box : 2685, Ajman - United Arab Emirates, Tel. : 00971 - 6 - 7436521, Fax : 00971 - 6 - 7439709
E-mail : ugl@emirates.net.ae, Website : www.unitedgrease.com



SYMBOL[S] NONE
R PHRASE[S] NONE
S PHRASE[S] NONE

OTHER INFORMATION:


R-PHRASES LISTED IN CHAPTER 2: R41 RISK OF SERIOUS DAMAGE TO EYES

R51/53 TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT

PRODUCT INFORMATION: FOR SPECIFIC OR DETAILED TECHNICAL DATA FOR THIS PRODUCT, PLEASE CONTACT YOUR LOCAL SALES REPRESENTATIVE.

HAZARD RATINGS : 4- Extreme
3- Serious
2- Moderate
1- Slight
0- Minimal
See section 8 for more detailed
Information on personal protection

The customer is responsible for determining



NOTICE FOR READER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user.

The contents and format of this MSDS are in accordance with EEC Commission Directive 93/112/EEC.

49 F/49

Revision:00

Issue Date:24/01/20



ISO 9001: 2008
Reg No : RI91/6709