

## **MATERIAL SAFETY DATA SHEET**

PRODUCT

CODE COMPANY IDENTIFICATION RUXX OIL ULTRA (S.A.E 5W/40 API SL/CF) UGL17ABXXYY M/s UNITED GREASE AND LUBRICANTS P.O. BOX 2685 AJMAN U.A.E. 00971-6-7436521 ULTRA GASOLINE ENGINE OIL

EMERGENCY PHONE NUMBER: PRODUCT USE :

#### **COMPOSITION / INFORMATION ON INGREDIENTS**

CHEMICAL NAME	WT %
Calcium branched alkylphenol and overbase sulfonates	2-6%
Zinc Alkyl dithiophosphates	0-15%
Organo molybdenum amide	0.5%
Distillates (petroleum), hydro treated heavy paraffines	35-40%
Distillates (petroleum), hydro treated light paraffinic	60-65%

# HAZARDS IDENTIFICATION

UNDER NORMAL CONDITIONS OF USE, THIS PRODUCT SHOULD NOT CAUSE ANY SIGNIFICANT HEALTH HAZARDS.HOW EVER A PROLONGED USE MAY CAUSE DERMATITIS.

<u>FIRST</u>	AID	MEASURES	:

:

SKIN CONTACT

EYE CONTACT

INGESTION

INHALATION

REMOVE CONTAMINATED CLOTHING, WASH SKIN IMMEDIATELY WITH WATER AND SOAP

FLUSH WITH LARGE AMOUNT OFWATER, GET MEDICAL ATTENTION IF IRRITATION PERSISTS

DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IN CASE OF EXPOSURE TO HIGH CONCENTRATION REMOVE PERSON TO FRESH AIR



می.ب : ۲٦٨٥، عجمان – ا.ع.م.، تلیفون : ۲۹۷۱ – ۲ – ۷٤۳۹۷۷ – ۲ – ۹۷۱ – ۲ به اکس : ۹۰۹۷۹ – ۲ – ۹۷۱ – ۹۷۱ – ۹۷۱ – ۹۷۱ P.O. Box : 2685, Ajman - United Arab Emirates, Tel. : 00971 - 6 - 7436521, Fax : 00971 - 6 - 7439709 E-mail : ugl@emirates.net.ae, Website : www.unitedgrease.com



FIRE FIGHTING MEASURES	S				
FLASH POINT : EXTINGUISHING MEDIA :		220 Deg C CO2, DRY CHEMICAL, OR FOAM.WATER SPRAY, DO NOT USE WATER JETS .THEY COULD CAUSE SPLATTERING.			
ACCIDENTAL RELEASE MEASURES					
ENVIRONMENTAL PROTECTION	:	SHUT OFF SOURCE OF SPILL .RECOVER FREE LIQUIDS BY USING APPROPRIATE			
HANDLING AND STORAGE	:	TECHNIQUES.NOTIFY LOCAL AUTHORITIES HANDLING AND STORAGE TEMP. AMBIENT TO 85 Deg C			
EXPOSURECONTROLS/PE	RSON	JAL PROTECTION.			
HAND/EYES/SKIN PROTECTION	:	WEAR GOGGLES, PROTECTIVE CLOTHING			
VENTILATION	:	, GLOVES. NO SPECIAL VENTILATION REQUIRED			
PHYSICAL AND CHEMICAL PROPERTIES					
APPEARANANCE	:	C&B			
ODOUR	:	CHARACTERISTIC			
COLOR DENSITY @ 15 Deg	:	GOLDEN 0.875 g/ml			
FLASH POINT	•	220 Deg C			
SOLUBLITY	:	SOLUBLE IN HYDROCARBON SOLVENTS, INSOLUBLE IN WATER			
STABILITY AND REACTIVIT	Ϋ́				
STABILITY	:	STABLE PRODUCT			
HAZARDOUS REACTION ECOLOGICAL INFORMATION	:	NONE			
GENERAL	:	NO SPECIFIC ENVIRONMENTAL DATA AVAILABLE			
<b>DISPOSAL CONSIDERATIC</b>	N				
DISPOSAL OF PRODUCT	:	DO NOT DISPOSE OF THE PRODUCT EITHER NEW OR USED, BY DISCHARGING IN TO SEWERS, TUNNELS, LAKES OR WATER			
		COURSES.			
TRANSPORT INFORMATIO		:			
NOT DANGEROUS FOR CONVEYAN UNDER UN, IMO, ADR/RID AND	NCE	NOT REGULATED			
IATA/CAO CODES	•				
JAS-ANZ					

 ISO 9001 : 2008

 Reg No : RI91/6709

می.ب : ۲۵۸۵، عجمان–۱.ع.م.، تلیفون : ۲۵۵٬۵۲۱–۲–۷۷۲۰۰، فاکس : ۷۹۷۰۹–۲–۷۷۹۷۰ P.O. Box : 2685, Ajman - United Arab Emirates, Tel. : 00971 - 6 - 7436521, Fax : 00971 - 6 - 7439709 E-mail : ugl@emirates.net.ae, Website : www.unitedgrease.com



### **REGULATORY INFORMATION:**

SYMBOL[S]	NONE
R PHRASE[S]	NONE
S PHRASE[S]	NONE

#### **OTHER INFORMATIONS:**

R-PHRASES LISTED IN CHAPTER 2: R41 RISK OF SERIOUS DAMAGE TO EYES R51/53 TOXIC TO ACQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT PRODUCT INFORMATION: FOR SPECIFIC OR DETAILED TECHNICAL DATA FOR THIS PRODUCT, PLEASE CONTACT YOUR LOCAL SALES REPRESENTATIVE.


HAZARD RATINGS

- 4- Extreme
  - 3- Serious
  - 2- Moderate
  - 1-Slight
- 0- Minimal

See section 8 for more detailed

Information on personal protection

The customer is responsible for determining



#### NOTICE FOR READER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user.

The contents and format of this MSDS are in accordance with EEC Commission Directive 93/112/EEC.

49 F/49

Revision:00

Issue Date:24/01/20



ص.ب : ۲۵۸۵، عجمان – ۱. ع.م.، تليفون : ۲۹۷۱ – ۲ – ۲ ۹۷۱ – ۲ – ۲ ۹۷۱ مناکس : ۲۰۹۷۱ – ۲. ۹۷۱ – ۲. ۹۷۱ P.O. Box : 2685, Ajman - United Arab Emirates, Tel. : 00971 - 6 - 7436521, Fax : 00971 - 6 - 7439709 E-mail : ugl@emirates.net.ae, Website : www.unitedgrease.com